

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
0	read	man/ cs/	0	unsigned int fd	char *buf	size_t count	-	-	-
1	write	man/ cs/	1	unsigned int fd	const char *buf	size_t count	-	-	-
2	open	man/ cs/	2	const char *filename	int flags	umode_t mode	-	-	-
3	close	man/ cs/	3	unsigned int fd	-	-	-	-	-
4	stat	man/ cs/	4	const char *filename	struct __old_kernel_stat *statbuf	-	-	-	-
5	fstat	man/ cs/	5	unsigned int fd	struct __old_kernel_stat *statbuf	-	-	-	-
6	lstat	man/ cs/	6	const char *filename	struct __old_kernel_stat *statbuf	-	-	-	-
7	poll	man/ cs/	7	struct pollfd *ufds	unsigned int nfds	int timeout	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
8	lseek	man/ cs/	8	unsigned int fd	off_t offset	unsigned int whence	-	-	-
9	mmap	man/ cs/	9	?	?	?	?	?	?
10	mprotect	man/ cs/	A	unsigned long start	size_t len	unsigned long prot	-	-	-
11	munmap	man/ cs/	B	unsigned long addr	size_t len	-	-	-	-
12	brk	man/ cs/	C	unsigned long brk	-	-	-	-	-
13	rt_sigaction	man/ cs/	D	int	const struct sigaction *	struct sigaction *	size_t	-	-
14	rt_sigprocmask	man/ cs/	E	int how	sigset_t *set	sigset_t *oset	size_t sigsetsize	-	-
15	rt_sigreturn	man/ cs/	F	?	?	?	?	?	?
16	ioctl	man/ cs/	10	unsigned int fd	unsigned int cmd	unsigned long arg	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
17	pread64	man/ cs/	11	unsigned int fd	char *buf	size_t count	loff_t pos	-	-
18	pwrite64	man/ cs/	12	unsigned int fd	const char *buf	size_t count	loff_t pos	-	-
19	readv	man/ cs/	13	unsigned long fd	const struct iovec *vec	unsigned long vlen	-	-	-
20	writelv	man/ cs/	14	unsigned long fd	const struct iovec *vec	unsigned long vlen	-	-	-
21	access	man/ cs/	15	const char *filename	int mode	-	-	-	-
22	pipe	man/ cs/	16	int *fildes	-	-	-	-	-
23	select	man/ cs/	17	int n	fd_set *inp	fd_set *outp	fd_set *exp	struct timeval *tvp	-
24	sched_yield	man/ cs/	18	-	-	-	-	-	-
25	mremap	man/ cs/	19	unsigned long addr	unsigned long old_len	unsigned long new_len	unsigned long flags	unsigned long new_addr	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
26	msync	man/ cs/	1A	unsigned long start	size_t len	int flags	-	-	-
27	mincore	man/ cs/	1B	unsigned long start	size_t len	unsigned char * vec	-	-	-
28	madvise	man/ cs/	1C	unsigned long start	size_t len	int behavior	-	-	-
29	shmget	man/ cs/	1D	key_t key	size_t size	int flag	-	-	-
30	shmat	man/ cs/	1E	int shmid	char *shmaddr	int shmflg	-	-	-
31	shmctl	man/ cs/	1F	int shmid	int cmd	struct shmids *buf	-	-	-
32	dup	man/ cs/	20	unsigned int fildes	-	-	-	-	-
33	dup2	man/ cs/	21	unsigned int oldfd	unsigned int newfd	-	-	-	-
34	pause	man/ cs/	22	-	-	-	-	-	-
35	nanosleep	man/ cs/	23	struct __kernel_timespec *rqtp	struct __kernel_timespec *rmtp	int	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
36	getitimer	man/ cs/	24	int which	struct itimerval *value	-	-	-	-
37	alarm	man/ cs/	25	unsigned int seconds	-	-	-	-	-
38	setitimer	man/ cs/	26	int which	struct itimerval *value	struct itimerval *ovalue	-	-	-
39	getpid	man/ cs/	27	-	-	-	-	-	-
40	sendfile	man/ cs/	28	int out_fd	int in_fd	off_t *offset	size_t count	-	-
41	socket	man/ cs/	29	int	int	int	-	-	-
42	connect	man/ cs/	2A	int	struct sockaddr *	int	-	-	-
43	accept	man/ cs/	2B	int	struct sockaddr *	int *	-	-	-
44	sendto	man/ cs/	2C	int	void *	size_t	unsigned	struct sockaddr *	int
45	recvfrom	man/ cs/	2D	int	void *	size_t	unsigned	struct sockaddr *	int *

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
46	sendmsg	man/ cs/	2E	int fd	struct user_msghdr *msg	unsigned flags	-	-	-
47	recvmsg	man/ cs/	2F	int fd	struct user_msghdr *msg	unsigned flags	-	-	-
48	shutdown	man/ cs/	30	int	int	-	-	-	-
49	bind	man/ cs/	31	int	struct sockaddr *	int	-	-	-
50	listen	man/ cs/	32	int	int	-	-	-	-
51	getsockname	man/ cs/	33	int	struct sockaddr *	int *	-	-	-
52	getpeername	man/ cs/	34	int	struct sockaddr *	int *	-	-	-
53	socketpair	man/ cs/	35	int	int	int	int *	-	-
54	setsockopt	man/ cs/	36	int fd	int level	int optname	char *optval	int optlen	-
55	getsockopt	man/ cs/	37	int fd	int level	int optname	char *optval	int *optlen	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
56	clone	man/ cs/	38	unsigned long	unsigned long	int *	int *	unsigned long	-
57	fork	man/ cs/	39	-	-	-	-	-	-
58	vfork	man/ cs/	3A	-	-	-	-	-	-
59	execve	man/ cs/	3B	const char *filename	const char *const *argv	const char *const *envp	-	-	-
60	exit	man/ cs/	3C	int error_code	-	-	-	-	-
61	wait4	man/ cs/	3D	pid_t pid	int *stat_addr	int options	struct rusage *ru	-	-
62	kill	man/ cs/	3E	pid_t pid	int sig	-	-	-	-
63	uname	man/ cs/	3F	struct old_utsname *	-	-	-	-	-
64	semget	man/ cs/	40	key_t key	int nsems	int semflg	-	-	-
65	semop	man/ cs/	41	int semid	struct sembuf *sops	unsigned nsops	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
66	semctl	man/ cs/	42	int semid	int semnum	int cmd	unsigned long arg	-	-
67	shmdt	man/ cs/	43	char *shmaddr	-	-	-	-	-
68	msgget	man/ cs/	44	key_t key	int msgflg	-	-	-	-
69	msgsnd	man/ cs/	45	int msqid	struct msgbuf *msgp	size_t msgsz	int msgflg	-	-
70	msgrcv	man/ cs/	46	int msqid	struct msgbuf *msgp	size_t msgsz	long msgtyp	int msgflg	-
71	msgctl	man/ cs/	47	int msqid	int cmd	struct msqid_ds *buf	-	-	-
72	fcntl	man/ cs/	48	unsigned int fd	unsigned int cmd	unsigned long arg	-	-	-
73	flock	man/ cs/	49	unsigned int fd	unsigned int cmd	-	-	-	-
74	fsync	man/ cs/	4A	unsigned int fd	-	-	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
75	fdatasync	man/ cs/	4B	unsigned int fd	-	-	-	-	-
76	truncate	man/ cs/	4C	const char *path	long length	-	-	-	-
77	ftruncate	man/ cs/	4D	unsigned int fd	unsigned long length	-	-	-	-
78	getdents	man/ cs/	4E	unsigned int fd	struct linux_dir *dirent	unsigned int count	-	-	-
79	getcwd	man/ cs/	4F	char *buf	unsigned long size	-	-	-	-
80	chdir	man/ cs/	50	const char *filename	-	-	-	-	-
81	fchdir	man/ cs/	51	unsigned int fd	-	-	-	-	-
82	rename	man/ cs/	52	const char *oldname	const char *newname	-	-	-	-
83	mkdir	man/ cs/	53	const char *pathname	umode_t mode	-	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
84	rmdir	man/ cs/	54	const char *pathname	-	-	-	-	-
85	creat	man/ cs/	55	const char *pathname	umode_t mode	-	-	-	-
86	link	man/ cs/	56	const char *oldname	const char *newname	-	-	-	-
87	unlink	man/ cs/	57	const char *pathname	-	-	-	-	-
88	symlink	man/ cs/	58	const char *old	const char *new	-	-	-	-
89	readlink	man/ cs/	59	const char *path	char *buf	int bufsiz	-	-	-
90	chmod	man/ cs/	5A	const char *filename	umode_t mode	-	-	-	-
91	fchmod	man/ cs/	5B	unsigned int fd	umode_t mode	-	-	-	-
92	chown	man/ cs/	5C	const char *filename	uid_t user	gid_t group	-	-	-

NR	SYS CALL NAME	reference	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
93	fchown	man/cs/	5D	unsigned int fd	uid_t user	gid_t group	-	-	-
94	lchown	man/cs/	5E	const char *filename	uid_t user	gid_t group	-	-	-
95	umask	man/cs/	5F	int mask	-	-	-	-	-
96	gettimeofday	man/cs/	60	struct timeval *tv	struct timezone *tz	-	-	-	-
97	getrlimit	man/cs/	61	unsigned int resource	struct rlimit *rlim	-	-	-	-
98	getrusage	man/cs/	62	int who	struct rusage *ru	-	-	-	-
99	sysinfo	man/cs/	63	struct sysinfo *info	-	-	-	-	-
100	times	man/cs/	64	struct tms *tbuf	-	-	-	-	-
101	ptrace	man/cs/	65	long request	long pid	unsigned long addr	unsigned long data	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
102	getuid	man/ cs/	66	-	-	-	-	-	-
103	syslog	man/ cs/	67	int type	char *buf	int len	-	-	-
104	getgid	man/ cs/	68	-	-	-	-	-	-
105	setuid	man/ cs/	69	uid_t uid	-	-	-	-	-
106	setgid	man/ cs/	6A	gid_t gid	-	-	-	-	-
107	geteuid	man/ cs/	6B	-	-	-	-	-	-
108	getegid	man/ cs/	6C	-	-	-	-	-	-
109	setpgid	man/ cs/	6D	pid_t pid	pid_t pgid	-	-	-	-
110	getppid	man/ cs/	6E	-	-	-	-	-	-
111	getpgrp	man/ cs/	6F	-	-	-	-	-	-
112	setsid	man/ cs/	70	-	-	-	-	-	-
113	setreuid	man/ cs/	71	uid_t ruid	uid_t euid	-	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
114	setregid	man/ cs/	72	gid_t rgid	gid_t egid	-	-	-	-
115	getgroups	man/ cs/	73	int gidsetsizes	gid_t groupplist	-	-	-	-
116	setgroups	man/ cs/	74	int gidsetsizes	gid_t groupplist	-	-	-	-
117	setresuid	man/ cs/	75	uid_t ruid	uid_t euid	uid_t suid	-	-	-
118	getresuid	man/ cs/	76	uid_t *ruid	uid_t *euid	uid_t *suid	-	-	-
119	setresgid	man/ cs/	77	gid_t rgid	gid_t egid	gid_t sgid	-	-	-
120	getresgid	man/ cs/	78	gid_t *rgid	gid_t *egid	gid_t *sgid	-	-	-
121	getpgid	man/ cs/	79	pid_t pid	-	-	-	-	-
122	setfsuid	man/ cs/	7A	uid_t uid	-	-	-	-	-
123	setfsgid	man/ cs/	7B	gid_t gid	-	-	-	-	-
124	getsid	man/ cs/	7C	pid_t pid	-	-	-	-	-
125	capget	man/ cs/	7D	cap_user header	cap_user data_ptr	data_t	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
126	capset	man/ cs/	7E	cap_user_header	const header_t cap_user_data_t data	-	-	-	-
127	rt_sigpending	man/ cs/	7F	sigset_t *set	size_t sigsetsize	-	-	-	-
128	rt_sigtimedwait	man/ cs/	80	const sigset_t *uthese	siginfo_t *uinfo	const struct __kernel_timespec *uts	size_t sigsetsize	-	-
129	rt_sigqueueinfo	man/ cs/	81	pid_t pid	int sig	siginfo_t *uinfo	-	-	-
130	rt_sigsuspend	man/ cs/	82	sigset_t *unewsets	size_t sigsetsize	-	-	-	-
131	sigaltstack	man/ cs/	83	const struct sigaltstack *uss	struct sigaltstack *uoss	-	-	-	-
132	utime	man/ cs/	84	char *filename	struct utimbuf *times	-	-	-	-
133	mknod	man/ cs/	85	const char *filename	umode_t mode	unsigned dev	-	-	-
134	uselib	man/ cs/	86	const char *library	-	-	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
135	personality	man/ cs/	87	unsigned int personality	-	-	-	-	-
136	ustat	man/ cs/	88	unsigned dev	struct ustat *ubuf	-	-	-	-
137	statfs	man/ cs/	89	const char * path	struct statfs *buf	-	-	-	-
138	fstatfs	man/ cs/	8A	unsigned int fd	struct statfs *buf	-	-	-	-
139	sysfs	man/ cs/	8B	int option	unsigned long arg1	unsigned long arg2	-	-	-
140	getpriority	man/ cs/	8C	int which	int who	-	-	-	-
141	setpriority	man/ cs/	8D	int which	int who	int niceval	-	-	-
142	sched_setparam	man/ cs/	8E	pid_t pid	struct sched_param *param		-	-	-
143	sched_getparam	man/ cs/	8F	pid_t pid	struct sched_param *param		-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
144	sched_setscheduler	man/ cs/	90	pid_t pid	int policy	struct sched_param *param	-	-	-
145	sched_getscheduler	man/ cs/	91	pid_t pid	-	-	-	-	-
146	sched_get_priority_max	man/ cs/	92	int policy	-	-	-	-	-
147	sched_get_priority_min	man/ cs/	93	int policy	-	-	-	-	-
148	sched_rr_get_interval	man/ cs/	94	pid_t pid	struct __kernel_timespec *interval	-	-	-	-
149	mlock	man/ cs/	95	unsigned long start	size_t len	-	-	-	-
150	munlock	man/ cs/	96	unsigned long start	size_t len	-	-	-	-
151	mlockall	man/ cs/	97	int flags	-	-	-	-	-
152	munlockall	man/ cs/	98	-	-	-	-	-	-
153	vhangup	man/ cs/	99	-	-	-	-	-	-
154	modify_ldt	man/ cs/	9A	?	?	?	?	?	?

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
155	pivot_root	man/cs/	9B	const char *new_root	const char *put_old	-	-	-	-
156	_sysctl	man/cs/	9C	?	?	?	?	?	?
157	prctl	man/cs/	9D	int option	unsigned long arg2	unsigned long arg3	unsigned long arg4	unsigned long arg5	-
158	arch_prctl	man/cs/	9E	?	?	?	?	?	?
159	adjtimex	man/cs/	9F	struct __kernel_timex *txc_p		-	-	-	-
160	setrlimit	man/cs/	A0	unsigned int resource	struct rlimit *rlim	-	-	-	-
161	chroot	man/cs/	A1	const char *filename	-	-	-	-	-
162	sync	man/cs/	A2	-	-	-	-	-	-
163	acct	man/cs/	A3	const char *name	-	-	-	-	-
164	settimeofday	man/cs/	A4	struct timeval *tv	struct timezone *tz	-	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
165	mount	man/ cs/	A5	char *dev_name	char *dir_name	char *type	unsigned long flags	void *data	-
166	umount2	man/ cs/	A6	?	?	?	?	?	?
167	swapon	man/ cs/	A7	const char *specialfile	int swap_flags	-	-	-	-
168	swapoff	man/ cs/	A8	const char *specialfile	-	-	-	-	-
169	reboot	man/ cs/	A9	int magic1	int magic2	unsigned int cmd	void *arg	-	-
170	sethostname	man/ cs/	AA	char *name	int len	-	-	-	-
171	setdomainname	man/ cs/	AB	char *name	int len	-	-	-	-
172	iopl	man/ cs/	AC	?	?	?	?	?	?
173	ioperm	man/ cs/	AD	unsigned long from	unsigned long num	int on	-	-	-
174	create_module	man/ cs/	AE	?	?	?	?	?	?

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
175	init_module	man/ cs/	AF	void *umod	unsigned long len	const char *uargs	-	-	-
176	delete_module	man/ cs/	B0	const char *name_user	unsigned int flags	-	-	-	-
177	get_kernel_syms	man/ cs/	B1	?	?	?	?	?	?
178	query_module	man/ cs/	B2	?	?	?	?	?	?
179	quotactl	man/ cs/	B3	unsigned int cmd	const char *special	qid_t id	void *addr	-	-
180	nfsservctl	man/ cs/	B4	?	?	?	?	?	?
181	getpmsg	man/ cs/	B5	?	?	?	?	?	?
182	putpmsg	man/ cs/	B6	?	?	?	?	?	?
183	afs_syscall	man/ cs/	B7	?	?	?	?	?	?
184	tuxcall	man/ cs/	B8	?	?	?	?	?	?
185	security	man/ cs/	B9	?	?	?	?	?	?

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
186	gettid	man/ cs/	BA	-	-	-	-	-	-
187	readahead	man/ cs/	BB	int fd	loff_t offset	size_t count	-	-	-
188	setxattr	man/ cs/	BC	const char *path	const char *name	const void *value	size_t size	int flags	-
189	lsetxattr	man/ cs/	BD	const char *path	const char *name	const void *value	size_t size	int flags	-
190	fsetxattr	man/ cs/	BE	int fd	const char *name	const void *value	size_t size	int flags	-
191	getxattr	man/ cs/	BF	const char *path	const char *name	void *value	size_t size	-	-
192	lgetxattr	man/ cs/	C0	const char *path	const char *name	void *value	size_t size	-	-
193	fgetxattr	man/ cs/	C1	int fd	const char *name	void *value	size_t size	-	-
194	listxattr	man/ cs/	C2	const char *path	char *list	size_t size	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
195	llexattr	man/ cs/	C3	const char *path	char *list	size_t size	-	-	-
196	fllexattr	man/ cs/	C4	int fd	char *list	size_t size	-	-	-
197	removexattr	man/ cs/	C5	const char *path	const char *name	-	-	-	-
198	lremovexattr	man/ cs/	C6	const char *path	const char *name	-	-	-	-
199	fremovexattr	man/ cs/	C7	int fd	const char *name	-	-	-	-
200	tkill	man/ cs/	C8	pid_t pid	int sig	-	-	-	-
201	time	man/ cs/	C9	time_t *tloc	-	-	-	-	-
202	futex	man/ cs/	CA	u32 *uaddr	int op	u32 val	struct __kernel_timespec *utime	u32 *uaddr2	u32 val3
203	sched_setaffinity	man/ cs/	CB	pid_t pid	unsigned int len	unsigned long *user_mask_ptr	-	-	-
204	sched_getaffinity	man/ cs/	CC	pid_t pid	unsigned int len	unsigned long *user_mask_ptr	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
205	set_thread_area	man/cs/	CD	?	?	?	?	?	?
206	io_setup	man/cs/	CE	unsignedaio_context_t nr_reqs	*ctx	-	-	-	-
207	io_destroy	man/cs/	CF	aio_context_t ctx	-	-	-	-	-
208	io_getevents	man/cs/	D0	aio_context_t ctx_id	long min_nr	long nr	struct io_event *events	struct __kernel_timespec *timeout	-
209	io_submit	man/cs/	D1	aio_context_t ctx_id	long nr	struct iocb * *	-	-	-
210	io_cancel	man/cs/	D2	aio_context_t ctx_id	struct iocb *iocb	struct io_event *result	-	-	-
211	get_thread_area	man/cs/	D3	?	?	?	?	?	?
212	lookup_dcookie	man/cs/	D4	u64 cookie	char 64 *buf	size_t len	-	-	-
213	epoll_create	man/cs/	D5	int size	-	-	-	-	-
214	epoll_ctl_old	man/cs/	D6	?	?	?	?	?	?
215	epoll_wait_old	man/cs/	D7	?	?	?	?	?	?

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
216	remap_file_pages	man/ cs/	D8	unsigned long start	unsigned long size	unsigned long prot	unsigned long pgoff	unsigned long flags	-
217	getdents64	man/ cs/	D9	unsigned int fd	struct linux_dir *dirent	unsigned int64 count	-	-	-
218	set_tid_address	man/ cs/	DA	int *tidptr	-	-	-	-	-
219	restart_syscall	man/ cs/	DB	-	-	-	-	-	-
220	semtimedop	man/ cs/	DC	int semid	struct sembuf *sops	unsigned nsops	const struct __kernel_timespec *timeout	-	-
221	fadvise64	man/ cs/	DD	int fd	loff_t offset	size_t len	int advice	-	-
222	timer_create	man/ cs/	DE	clockid_t which_clock	struct sigevent *timer_event	timer_t *timer_id	-	-	-
223	timer_settime	man/ cs/	DF	timer_t timer_id	int flags	const struct __kernel_itimerspec *new_setting	struct kernel_itimerspec *old_setting	-	-
224	timer_gettime	man/ cs/	E0	timer_t timer_id	struct __kernel_itimerspec *setting	-	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
225	timer_getoverrun	man/ cs/	E1	timer_t timer_id	-	-	-	-	-
226	timer_delete	man/ cs/	E2	timer_t timer_id	-	-	-	-	-
227	clock_settime	man/ cs/	E3	clockid_t which_clock	const struct kernel_timespec *tp	-	-	-	-
228	clock_gettime	man/ cs/	E4	clockid_t which_clock	struct kernel_timespec *tp	-	-	-	-
229	clock_getres	man/ cs/	E5	clockid_t which_clock	struct kernel_timespec *tp	-	-	-	-
230	clock_nanosleep	man/ cs/	E6	clockid_t which_clock	int flags	const struct __kernel_timespec *rqtp	struct kernel_timespec *rmtp	-	-
231	exit_group	man/ cs/	E7	int error_code	-	-	-	-	-
232	epoll_wait	man/ cs/	E8	int epfd	struct epoll_event *events	int maxevents	int timeout	-	-
233	epoll_ctl	man/ cs/	E9	int epfd	int op	int fd	struct epoll_event *event	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
234	tgkill	man/ cs/	EA	pid_t tgid	pid_t pid	int sig	-	-	-
235	utimes	man/ cs/	EB	char *filename	struct timeval *utimes	-	-	-	-
236	vserver	man/ cs/	EC	?	?	?	?	?	?
237	mbind	man/ cs/	ED	unsigned long start	unsigned long len	unsigned long mode	const unsigned long *nmask	unsigned long maxnode	unsigned flags
238	set_mempolicy	man/ cs/	EE	int mode	const unsigned long *nmask	unsigned long maxnode	-	-	-
239	get_mempolicy	man/ cs/	EF	int *policy	unsigned long *nmask	unsigned long maxnode	unsigned long addr	unsigned long flags	-
240	mq_open	man/ cs/	F0	const char *name	int oflag	umode_t mode	struct mq_attr *attr	-	-
241	mq_unlink	man/ cs/	F1	const char *name	-	-	-	-	-
242	mq_timedsend	man/ cs/	F2	mqd_t mqdes	const char *msg_ptr	size_t msg_len	unsigned int msg_prio	const struct __kernel_timespec *abs_timeout	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
243	mq_timedreceive	man/ cs/	F3	mqd_t mqdes	char *msg_ptr	size_t msg_len	unsigned int *msg_prio	const struct _kernel_timespec *abs_timeout	-
244	mq_notify	man/ cs/	F4	mqd_t mqdes	const struct sigevent *notification	-	-	-	-
245	mq_getsetattr	man/ cs/	F5	mqd_t mqdes	const struct mq_attr *mqstat	struct mq_attr *omqstat	-	-	-
246	kexec_load	man/ cs/	F6	unsigned long entry	unsigned long nr_segments	struct kexec_segment *segments	unsigned long flags	-	-
247	waitid	man/ cs/	F7	int which	pid_t pid	struct siginfo *infop	int options	struct rusage *ru	-
248	add_key	man/ cs/	F8	const char *_type	const char *_description	const void *_payload	size_t plen	key_serial_t destringid	-
249	request_key	man/ cs/	F9	const char *_type	const char *_description	const char *_payload	key_serial_t destringid *_out_info	-	-
250	keyctl	man/ cs/	FA	int cmd	unsigned long arg2	unsigned long arg3	unsigned long arg4	unsigned long arg5	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
251	ioprio_set	man/ cs/	FB	int which	int who	int ioprio	-	-	-
252	ioprio_get	man/ cs/	FC	int which	int who	-	-	-	-
253	inotify_init	man/ cs/	FD	-	-	-	-	-	-
254	inotify_add_watch	man/ cs/	FE	int fd	const char *path	u32 mask	-	-	-
255	inotify_rm_watch	man/ cs/	FF	int fd	__s32 wd	-	-	-	-
256	migrate_pages	man/ cs/	100	pid_t pid	unsigned long maxnode	const unsigned long *from	const unsigned long *to	-	-
257	openat	man/ cs/	101	int dfd	const char *filename	int flags	umode_t mode	-	-
258	mkdirat	man/ cs/	102	int dfd	const char * pathname	umode_t mode	-	-	-
259	mknodat	man/ cs/	103	int dfd	const char * filename	umode_t mode	unsigned dev	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
260	fchownat	man/cs/	104	int dfd	const char *filename	uid_t user	gid_t group	int flag	-
261	futimesat	man/cs/	105	int dfd	const char *filename	struct timeval utimes	-	-	-
262	newfstatat	man/cs/	106	int dfd	const char *filename	struct stat statbuf	int flag	-	-
263	unlinkat	man/cs/	107	int dfd	const char * pathname	int flag	-	-	-
264	renameat	man/cs/	108	int olddfd	const char * oldname	int newdfd	const char * newname	-	-
265	linkat	man/cs/	109	int olddfd	const char *oldname	int newdfd	const char *newname	int flags	-
266	symlinkat	man/cs/	10A	const char * oldname	int newdfd	const char * newname	-	-	-
267	readlinkat	man/cs/	10B	int dfd	const char *path	char *buf	int bufsiz	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
268	fchmodat	man/ cs/	10C	int dfd	const char * filename	umode_t mode	-	-	-
269	faccessat	man/ cs/	10D	int dfd	const char *filename	int mode	-	-	-
270	pselect6	man/ cs/	10E	int	fd_set *	fd_set *	fd_set *	struct __kernel_timespec *	void timespec *
271	ppoll	man/ cs/	10F	struct pollfd *	unsigned int	struct __kernel_timespec *	const timespec *	size_t	-
272	unshare	man/ cs/	110	unsigned long unshare_flags	-	-	-	-	-
273	set_robust_list	man/ cs/	111	struct robust_list *head	size_t len	-	-	-	-
274	get_robust_list	man/ cs/	112	int pid	struct robust_list * *head_ptr	size_t *len_ptr	-	-	-
275	splice	man/ cs/	113	int fd_in	loff_t *off_in	int fd_out	loff_t *off_out	size_t len	unsigned int flags

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
276	tee	man/ cs/	114	int fdin	int fdout	size_t len	unsigned int flags	-	-
277	sync_file_range	man/ cs/	115	int fd	loff_t offset	loff_t nbytes	unsigned int flags	-	-
278	vmsplice	man/ cs/	116	int fd	const struct iovec *iov	unsigned long nr_segs	unsigned int flags	-	-
279	move_pages	man/ cs/	117	pid_t pid	unsigned long nr_pages	const void * *pages	const int *nodes	int *status	int flags
280	utimensat	man/ cs/	118	int dfd	const char *filename	struct __kernel_timespec utimes	int flags	-	-
281	epoll_pwait	man/ cs/	119	int epfd	struct epoll_event *events	int maxevents	int timeout	const sigset_t *sigmask	size_t sigsets
282	signalfd	man/ cs/	11A	int ufd	sigset_t *user_mask	size_t zmask	-	-	-
283	timerfd_create	man/ cs/	11B	int clockid	int flags	-	-	-	-
284	eventfd	man/ cs/	11C	unsigned int count	-	-	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
285	fallocate	man/ cs/	11D	int fd	int mode	loff_t offset	loff_t len	-	-
286	timerfd_settime	man/ cs/	11E	int ufd	int flags	const struct __kernel_itimerspec *utmr	struct __kernel_itimerspec *otmr		
287	timerfd_gettime	man/ cs/	11F	int ufd	struct __kernel_itimerspec *otmr			-	-
288	accept4	man/ cs/	120	int	struct sockaddr * *	int *	int	-	-
289	signalfd4	man/ cs/	121	int ufd	sigset_t *user_mask	size_t mask	int flags	-	-
290	eventfd2	man/ cs/	122	unsigned int count	int flags	-	-	-	-
291	epoll_create1	man/ cs/	123	int flags	-	-	-	-	-
292	dup3	man/ cs/	124	unsigned int oldfd	unsigned int newfd	int flags	-	-	-
293	pipe2	man/ cs/	125	int *fildes	int flags	-	-	-	-
294	inotify_init1	man/ cs/	126	int flags	-	-	-	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
295	preadv	man/ cs/	127	unsigned long fd	const struct iovec *vec	unsigned long vlen	unsigned long pos_l	unsigned long pos_h	-
296	pwritev	man/ cs/	128	unsigned long fd	const struct iovec *vec	unsigned long vlen	unsigned long pos_l	unsigned long pos_h	-
297	rt_tgsigqueueinfo	man/ cs/	129	pid_t tgid	pid_t pid	int sig	siginfo_t *uinfo	-	-
298	perf_event_open	man/ cs/	12A	struct perf_event_attr *attr	pid_t pid	int cpu	int group_fd	unsigned long flags	-
299	recvmsg	man/ cs/	12B	int fd	struct mmsghdr *msg	unsigned int vlen	unsigned flags	struct __kernel_timespec *timeout	-
300	fanotify_init	man/ cs/	12C	unsigned int flags	unsigned int event_f_flags	-	-	-	-
301	fanotify_mark	man/ cs/	12D	int fanotify_fd	unsigned int flags	u64 mask	int fd	const char *pathname	-
302	prlimit64	man/ cs/	12E	pid_t pid	unsigned int resource	const struct rlimit64 *new_rlim	struct rlimit64 *old_rlim	-	-

NR	SYS CALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
303	name_to_handle_at	man/ cs/	12F	int dfd	const char *name	struct file_handle *handle	int *mnt_id	int flag	-
304	open_by_handle_at	man/ cs/	130	int mountdirfd	struct file_handle *handle	int flags	-	-	-
305	clock_adjtime	man/ cs/	131	clockid_t which_clock	struct kernel_timex *tx	-	-	-	-
306	syncfs	man/ cs/	132	int fd	-	-	-	-	-
307	sendmmsg	man/ cs/	133	int fd	struct mmsghdr *msg	unsigned int vlen	unsigned flags	-	-
308	setns	man/ cs/	134	int fd	int nstype	-	-	-	-
309	getcpu	man/ cs/	135	unsigned *cpu	unsigned *node	struct getcpu_cache *cache	-	-	-
310	process_vm_readv	man/ cs/	136	pid_t pid	const struct iovec *lvec	unsigned long liovcnt	const struct iovec *rvec	unsigned long riovcnt	unsigned long flags
311	process_vm_writev	man/ cs/	137	pid_t pid	const struct iovec *lvec	unsigned long liovcnt	const struct iovec *rvec	unsigned long riovcnt	unsigned long flags

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
312	kcmp	man/ cs/	138	pid_t pid1	pid_t pid2	int type	unsigned long idx1	unsigned long idx2	-
313	finit_module	man/ cs/	139	int fd	const char *uargs	int flags	-	-	-
314	sched_setattr	man/ cs/	13A	pid_t pid	struct sched_attr *attr	unsigned int flags	-	-	-
315	sched_getattr	man/ cs/	13B	pid_t pid	struct sched_attr *attr	unsigned int size	unsigned int flags	-	-
316	renameat2	man/ cs/	13C	int olddfd	const char *oldname	int newdfd	const char *newname	unsigned int flags	-
317	seccomp	man/ cs/	13D	unsigned int op	unsigned int flags	void *uargs	-	-	-
318	getrandom	man/ cs/	13E	char *buf	size_t count	unsigned int flags	-	-	-
319	memfd_create	man/ cs/	13F	const char *uname	unsigned int pflags	-	-	-	-
320	kexec_file_load	man/ cs/	140	int kernel_fd	int initrd_fd	unsigned long cmdline_len	const char *cmdline	unsigned long flags	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
321	bpf	man/ cs/	141	int cmd	union bpf_attr *attr	unsigned int size	-	-	-
322	execveat	man/ cs/	142	int dfd	const char *filename	const char *const *argv	const char *const *envp	int flags	-
323	userfaultfd	man/ cs/	143	int flags	-	-	-	-	-
324	membarrier	man/ cs/	144	int cmd	int flags	-	-	-	-
325	mlock2	man/ cs/	145	unsigned long start	size_t len	int flags	-	-	-
326	copy_file_range	man/ cs/	146	int fd_in	loff_t *off_in	int fd_out	loff_t *off_out	size_t len	unsigned int flags
327	preadv2	man/ cs/	147	unsigned long fd	const struct iovec *vec	unsigned long vlen	unsigned long pos_l	unsigned long pos_h	rwf_t flags
328	pwritev2	man/ cs/	148	unsigned long fd	const struct iovec *vec	unsigned long vlen	unsigned long pos_l	unsigned long pos_h	rwf_t flags
329	pkey_mprotect	man/ cs/	149	unsigned long start	size_t len	unsigned long prot	int pkey	-	-

NR	SYSCALL NAME	referen	RAX	ARG0 (rdi)	ARG1 (rsi)	ARG2 (rdx)	ARG3 (r10)	ARG4 (r8)	ARG5 (r9)
330	pkey_alloc	man/ cs/	14A	unsigned long flags	unsigned long init_val	-	-	-	-
331	pkey_free	man/ cs/	14B	int pkey	-	-	-	-	-
332	statx	man/ cs/	14C	int dfd	const char *path	unsigned flags	unsigned mask	struct statx *buffer	-

© 2024
:: TMZ